Technical Data Sheet

Divinol Hypoid-Getriebeöl DB SAE 80

Product description

Divinol Hypoid-Getriebeöl DB SAE 80 is an EP-gearbox oil for running-in and subsequent lubrication of heavily loaded final drives.

Specification

API GL-5; MIL-L-2105 D

Manufacturer performance

MAN 342 M1; MB-Approval 235.0; Renault GL-5; Voith 3.325-339; Volvo 97310 / 97316; ZF TE-ML 07A, 08, 16B/C/D, 17B, 19B, 21A

Characteristics

SAE Grade: 80W

Colour / DIN ISO 2049: L 3,0

Viscosity/40°C / ASTM D 7042 : 85 mm²/s

Viscosity/100°C / ASTM D 7042 : 10.5 mm²/s

Viscosity index / ASTM D 2270 : 110

Density/15°C / DIN EN ISO 12185: 0,890 g/cm³

Pour point / DIN ISO 3016: -25 °C

Flash point (Cleveland) / DIN ISO 2592: 200 °C

Application

Divinol Hypoid-Getriebeöl DB SAE 80 is suitable for heavily loaded gearboxes, steering gear and auxiliary gearboxes if permitted by the manufacturer.

80750 04/2017-80750-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





Technical Data Sheet

Divinol Hypoid-Getriebeöl DB SAE 80

80750 04/2017-80750-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





2/2