

Technical Data Sheet

Divinol Hypoid-Getriebeöl LS 90

Product description

Special hypoid gear oil with limited slip additive.

Specification

API GL-5 LS; MIL-L-2105D

Manufacturer performance

MAN 342 M1; MB-Approval 235.0; DAF; Volvo 97310+97316; Voith 3.325-339; Renault Axle; ZF TE-ML 05C/07A/16B/16C/16D/17B/19B/21A

Characteristics

SAE Grade:	90
Appearance:	brown, clear
Colour / DIN ISO 2049:	< 4,0
Viscosity/40°C / ASTM D 7042 :	160 mm ² /s
Viscosity/100°C / ASTM D 7042 :	16 mm ² /s
Viscosity index / ASTM D 2270 :	> 95
Density/15°C / DIN EN ISO 12185:	900 kg/m ³
Pour point / DIN ISO 3016:	< -20 °C
Flash point (Cleveland) / DIN ISO 2592:	< 190°C

Application

For use in heavily loaded axial gears and for self-locking differentials.

80780

04/2017-80780-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Hypoid-Getriebeöl LS 90

80780

04/2017-80780-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2