

Technical Data Sheet

Divinol High Liquid

Product description

- non water-miscible concrete release agent
- solvent-free
- for high-quality fair-faced concrete parts
- of low viscosity

Characteristics

| | |
|---|-----------------------|
| Colour / DIN ISO 2049: | 0,5 |
| Viscosity/20°C / ASTM D 7042 : | 9 mm ² /s |
| Density/15°C / DIN EN ISO 12185: | 840 kg/m ³ |
| Pour point / DIN ISO 3016: | -15°C |
| Flash point (Cleveland) / DIN ISO 2592: | >130°C |
| Water hazard class, concentrate: | 1 |

Application

Due to high quality base oils **Divinol High Liquid** can be used for the production of quality concrete parts. The product is suitable for different kinds of formwork, e. g. wood as well as coated formworks in the civil construction sector.

Divinol High Liquid can also be used as mixer protection in machines, construction and transport vehicles.

The use of **Divinol High Liquid** guarantees an easy and clean demoulding as well as optimum surface results.

Divinol High Liquid can be applied as delivered by spraying, brushing and rolling as thin as possible.

When used as intended, **Divinol High Liquid** has no negative influence on the subsequent treatments of the concrete surfaces (plaster, tiles, wallpaper, colour).

84810

04/2017-84810-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1