

Technical Data Sheet

Divinol Abschmierfett 2

Product description

- Calcium soap lubricating grease
- of even, smooth structure
- offers a good pumpability
- guarantees favourable low-temperature performance
- with water-repellent effect
- offers good corrosion protection
- classification K 2 C-40 as per DIN 51 825
- classification ISO-L-XDAHA 2 as per ISO/DIS 6743-9

Characteristics

Colour / Appearance:	brown, smooth
Thickening agent:	Calcium soap
Operating temperature range:	-40°C - +60°C
NLGI-class / DIN 51 818:	2
Base oil viscosity/40°C / ASTM D 7042:	36 mm ² /s
Water content / DIN 51 777/T1:	0,5 %
Dropping point / DIN ISO 2176:	> 90 °C
Worked penetration/0.1mm, 60 double strokes / DIN ISO 2137:	280
Water resistance / DIN 51807-1:	Evaluation level 0
Flow pressure at -40°C / DIN 51 805:	1000 hPa
Corrosion protection behaviour (EMCOR-test) / DIN 51 802:	0/0

Application

Divinol Abschmierfett 2 is suitable as conventional car grease for roller and slide bearings with low thermal load.

85051

04/2017-85051-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1