

# Technical Data Sheet

## Divinol Haftöl ISO 460

---

### Product description

- special lubricating oil on the basis of mineral oil
- with friction-reducing and anti-wear high-pressure additives
- contains anti aging and corrosion protection additives
- reduces the oil consumption due to a highly effective adhesive additive

### Characteristics

Colour / DIN ISO 2049:	lighter 3.5
Density/15°C / DIN EN ISO 12185:	900 kg/m <sup>3</sup>
Viscosity/40°C / ASTM D 7042 :	460 mm <sup>2</sup> /s
Flash point (Cleveland) / DIN ISO 2592:	> 220 °C
Pour point / DIN ISO 3016:	< -6 °C

### Application

**Divinol Haftöl ISO 460** is especially used as sliding and bearing oil and is frequently used for open lubricating points. **Divinol Haftöl ISO 460** is preferred used in the textile, printing, paper and woodworking industry.

Furthermore, the product is used as reciprocating saw oil for lubrication of bearings, articulations, bolts, sliding guides and transport chains at reciprocating saws.

The selection of the adequate viscosity depends on the type of the individual lubricating points, provided that the viscosity is not prescribed by the machine manufacturer.

86361

04/2017-86361-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1