

Technical Data Sheet

Divinol Mischerschutz Spezial

Product description

- universal mixer protection on the basis of mineral oil
- high corrosion protection

Characteristics

Colour / DIN ISO 2049:	lighter 4.5
Viscosity/20°C / ASTM D 7042 :	21 mm ² /s
Density/15°C / DIN EN ISO 12185:	890 kg/m ³
Pour point / DIN ISO 3016:	-15 °C
Flash point (Cleveland) / DIN ISO 2592:	> 130 °C
Giscode:	BTM 20
Water hazardous class:	1

Application

Divinol Mischerschutz Spezial is a mixer protection for universal use in concrete mixer trucks, concrete pumps, concrete mixing facilities, construction vehicles etc. It prevents the adhesion of concrete on steel, metal and painted surfaces. The product does not affect rubber and plastic material and it preserves all painted parts.

Divinol Mischerschutz Spezial should be applied daily before starting up the vehicles and construction machinery (application by spray gun, compressor, hand sprayer or brush!).

When using **Divinol Mischerschutz Spezial** the quality of the concrete will not be affected - provided that the processing instructions have been followed.

91560

04/2017-91560-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1