# **Technical Data Sheet**

### **Divinol Asphalt Plus WMB**

### **Product description**

- · water-soluble release agent for bitumen and asphalt
- · based on mineral oil

#### Characteristics

Colour / DIN ISO 2049: 5

Viscosity/20°C / ASTM D 7042 : 33 mm<sup>2</sup>/s

Density/15°C / DIN EN ISO 12185: 870kg/m<sup>3</sup>

Pour point / DIN ISO 3016: -20°C

Flash point (Cleveland) / DIN ISO 2592: >130°C

pH-value (10 % in distilled H2O) / DIN 51 369: 9,6

Water hazardous class:

#### **Application**

**Divinol Asphalt Plus WMB** is a water-miscible release agent for bitumen and asphalt mixing machines, very well suitable as release agent for wooden pallets for the production of concrete blocks.

Divinol Asphalt Plus WMB is also usable as a water-miscible formwork oil concentrate.

## Working concentration

Bitumen and asphalt mixing plants (depending on the bituminous mixture): 1:3 - 1:6 diluted with water

Formwork oil: 1:10 - 1:15 diluted with water

## Preparation of the emulsion

First add concentrate, then add water by stirring continuously.

94270 04/2017-94270-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





# **Technical Data Sheet**

# **Divinol Asphalt Plus WMB**

### **Storage**

The product as delivered (concentrate) is frost-resistant.

#### **Note / Attention**

Only mix quantities which can be consumed within one working day.

94270 04/2017-94270-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





2/2