

Technical Data Sheet

Divinol Surface Premium

Product description

- Release agent for high quality fair-faced concrete (SB3, SB4)
- on the basis of dearomatized solvent
- prevents pores and shrink holes
- high surface quality

Characteristics

Colour / DIN ISO 2049:	lighter 1.0
Viscosity/20°C / ASTM D 7042 :	2.2
Density/15°C / DIN EN ISO 12185:	800 kg/m ³
Pour point / DIN ISO 3016:	< -30 °C
Flash point (Abel Pensky) / DIN 51 755:	27 °C
Giscode:	BTM 50
Water hazardous class:	1

Application

Divinol Surface Premium is a release agent for high quality fair-faced concrete, preferably used in the engineering and construction sector. The product is suitable for all absorbent and non-absorbent formworks, e.g. phenolic resin formwork as well as formwork made of plastic material (polypropylene). Considering safety technical principles and regulations, usage on heated formworks is possible.

If used properly, **Divinol Surface Premium** does not influence negatively the subsequent treatment of the concrete surface (plastering, ceramics, wallpaper, paint).

Preparation of the emulsion

Divinol Surface Premium can be applied in the state at time of delivery by spraying, brushing or rolling without any problems.

96520

04/2017-96520-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Surface Premium

Storage

Recommended storage temperature: +5 °C up to max. +40 °C.

Note / Attention

Close packages after use to prevent evaporation of solvents and to prevent the entry of dirt.

96520

04/2017-96520-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2